

Goldhofer Aktiengesellschaft ° P.O. Box 1364 ° 87683 Memmingen

Alextrans SRL Com Tintesti Mr. Bogdan Barac Strada Principala Nr. 366 127643 Pogonele RO Tel. +49 8331 15-0 Fax +49 8331 15-239 info@goldhofer.com www.goldhofer.com

Sitz und Registergericht Memmingen / HRB 10871 St.Nr.: 138/115/50722 USt-IdNr.: DE 812882017 Vorstand: Matthias Ruppel (Vorsitzender) Rainer Auerbacher Lothar Holder Aufsichtsratsvorsitzender: Hans-Joachim Boekstegers

Contact

Tobias Leschensky |

Order acknowledgement no. VAU002830

31/01/2022

Dear Mr. Barac,

We thank you for the order placed with us for the following items, which we confirm under considerations of our General Terms and Conditions (Sale). We assure you of careful execution.

1 GOLDHOFER Turntable

1.1 Loading Decks

1.1.1 <u>1 Paar Turntable DS 100 suitable for #29031</u>

- Capacity of each 100 t
- Steel ball / socket joint between load table and distribution frame
- dimention turntable 944 mm x 2.560 mm
- Protection against detaching of the load table
- 1 pair of sliding shoes for the rear turntable
- Suitable for 2.750 mm und 3.000 mm wide modular trailers
- Fixation of distribution frame on the modular trailer by means of 1 pair of fixing bars
- weight approx 3.400 kg



Load Security

- 16 thread bushings M36 arranged around the table in horizontal direction
- 4 thread bushings M36 arranged on the table in vertical direction
- 4 pair of VLBG 7 included
- Horizontal lashing point for mounting a steel rope as a connection to the opposite turntable
- 1.1.1.1 1 x 30.000 mm electric cable for THP turntable
- 1.1.1.2 1 x 30.000 mm brake connection (yellow blue) with 3 relay valves
- 1.1.1.3 1 x self-tracking device for turntables 100 t
- 1.1.1.4 1 x wire-rope 30 m long for fixing the supply-lines

1.2 Painting

Pre-Treatment

 steel construction according to DIN 55928 as well as ISO-Standard 8501 SA 2.5 corundum blasted

Paint System

- primer coating with 2-K zinc-rich paint coat (89% zinc)
- second coating with EP/2-K-PUR etch primer
- third and fourth coating with 2K-PUR top coat
- cavities sealed with EP/PUR primer and 2K-PUR top coat
- paint system proofed with salt spray test DIN EN ISO 9227
- connecting components with zinc flake / zinc-nickel coating
- conservation with vapour stream resistant material

Painting

single colored final painting in NCS 1175 Scania paprika red

1.3 General system information

country specification

EU: sidelights, reflector strip (yellow)

• Components are prepared for brake system

1 x 15 polig, 24 Volt

Power supply from tracktor unit

24 V

ABS

vehicle voltage THPType of system

THP/ET

tyre size

285/70 R 19.5

• Hydraulic oil are suitable

moderate climate zone

Hydraulic oil for loading decks and accessories are suitable for

THP

All supply-lines (Electric-cable, ABS-cable, brake-lines, hydraulic-hoses ...) between Truck tractor unit and trailer are, due to EU-regulations, part of the delivery-scope of the Truck tractor and are not part of the delivery scope of the trailer-producer.



Order acknowledgement no. VAU002830

Due to the increased wattage of the electricity consumers in our vehicles, for the signal transfer Goldhofer requires the 15-pole socket according to ISO 12089 (cable cross-section min. 2,5 mm²). The adapters from a 15-pole socket according to ISO 12089 to two 7-pole sockets according to ISO 1185 and ISO 3737 which are available on the market are required by the standards to have a maximum cross-section of 1,5 mm². In reality the manufacturers use a cross section of only 1 mm². These small cross-sections are not sufficiently safe for the operation of our electrical system. Any use of the 7-pole adapters therefore happens on the customer's own risk and Goldhofer assumes no liability for possible consequential damages.

14 r inin / Vehicle acceptanc

1.4.1 Training/Induction

The price quoted includes a training session for your operating personnel at our factory in Memmingen. The training takes place together with the takeover of the vehicle.

ec ni documentation

- 1 x spare parts catalogue "easyPARTs" (online), German, English, Spanish, French and Portuguese (Brazilian) reversible
- 1 x operation and maintenance manual (Data carrier), romanian
- 1 x driver manual (hardcopy form), multi-lingual